

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 May 2004 (06.05.2004)

PCT

(10) International Publication Number
WO 2004/037737 A1

(51) International Patent Classification⁷: C03C 17/00,
17/36, B32B 17/10, B60J 1/02, H05B 3/86

(74) Agents: LE VAGUERSE, Sylvian et al.; Glaverbel -
Centre R & D, Department Intellectual Property, Rue de
l'Aurore, 2, B-6040 Jumet (BE).

(21) International Application Number:
PCT/EP2003/050745

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 22 October 2003 (22.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02079430.1 22 October 2002 (22.10.2002) EP

(84) Designated States (*regional*): Eurasian patent (AM, AZ,
BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE,
BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU,
IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

(71) Applicant (*for all designated States except US*):
GLAVERBEL [BE/BE]; Glaverbel, Chaussée de La
Hulpe, 166, B-1170 Bruxelles (BE).

Declaration under Rule 4.17:
— of inventorship (Rule 4.17(iv)) for US only

(72) Inventor; and

Published:
— with international search report

(75) Inventor/Applicant (*for US only*): ROQUINY, Philippe
[BE/BE]; Glaverbel - Centre R & D, Rue de l'Aurore, 2,
B-6040 Jumet (BE).

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: ELECTRICALLY HEATABLE SOLAR REFLECTIVE COATED GLAZING WITH WINDOWS IN COATING CON-
FIGURED, SHAPED AND DIMENSIONED IN SUCH A WAY AS TO MINIMISE INHOMOGENEOUS HEATING

(57) Abstract: A vehicle glazing panel having an electrically heatable radiationreflective coating layer, at least two bus bars adapted to relay electrical power to the coating layer and at least a window, in the coating layer, permeable to electromagnetic radiations, which, when submitted to a power of 1000 W/m² during 4 minutes, presents in a portion of the glazing panel delimited by the bus bars and not including the bus bars tips and their close periphery, a maximum temperature and a minimum temperature, such that the difference between the maximum temperature of the glazing panel with the window and the maximum temperature of the same glazing panel without window does not exceed 25 °C. This may be used to minimise perturbations to the heating of the glazing caused by the presence of the window permeable to electromagnetic radiations and/or provide more even heating over the entire windscreen.

WO 2004/037737 A1